







Oksys was born 12 years ago and belongs to the company Quadrante, (more than 20 years experience as hardware/software manufacturer for NC and textile business).

Oksys is now present in more than 30 countries worldwide with a total production of 2000 units (20% on OEM basis).

## Our goal is to follow all design and production process internally in order to guarantee the best:

- Reliability and Quality
- ♦ Flexibility and time to market response
- ♦ Know How and Experience

### **MAIN FEATURES:**









### **EASY AND QUICK TO USE: NO MISTAKES**

- All models are equipped with a Graphic display with Icons Menu
   INSTANT RECOGNITION OF THE ONGOING PROCEDURES
- Four buttons only to control every function of the unit UP/DOWN ENTER/EXIT ...and the job is done!
- ◆ Fully automatic unit with no taps NO MISTAKES REDUCED OPERATOR COSTS AUTOMATIC HOSES EVACUATION: precise charge AUTOMATIC PRESSURE TEST: after the service INCLUDED DATA BASE: quickly recall car info
- Advanced features in reduced sizes easy MOVEMENT AROUND THE WORKSHOP



# REDUCED SERVICE AND MAINTENANCE COSTS

- Thanks to Max Recovery Function we may recover up to 95% of refrigerant from the car according to SAE J2788 REDUCED VEHICLE MAINTENANCE COSTS
- Use of dehydrating filter up to 100 Kg refrigerant: AVOIDS FREQUENT FILTER CHANGES
- Long life Vacuum Pump oil: replacement every 80 hr LESS WORRIES FOR THE MAINTENANCE OF THE UNIT
- All internal components are **easy to access**REDUCED MAINTENANCE TIME





#### RELIABLE

- High precision electronic scale
   NO NEED FOR FREQUENT RE-CALIBRATION
- ◆ Accurate refrigerant charging of the A/C SYSTEM HIGH PERFORMANCE SERVICE AND CAR COMPRESSOR PROTECTION
- ◆ Test of the A/C system performance after the service PROFESSIONAL A/C MAINTENANCE WITH A PROOFED QUALITY
- ◆ Automatic self-diagnostic status check
  PREVENTS THE COST OF THE UNIT 'S UNPLANNED
  DOWNTIME

### **COMPLYING WITH SPECIALISTS' NEEDS**

- ◆ A wide range of R134A AND R1234YF UNITS FOR PASSENGER CARS, TRUCKS, COACHES AND AGRICULTURAL VEHICLES
- ◆ Leak test under pressure
  WITH THE USE OF NITROGEN OR FORMING
  GAS IS INCLUDED IN MOST OF OUR MODELS
- A software for the FLUSHING PROCEDURE cof the A/C systems with refrigerant is included in most models
- ◆ Ready for HYBRID VEHICLES
- ◆ DIAGNOSTIC KIT available
- An optional GAS IDENTIFIER can be embedded in the unit
- ◆ PC DATA TRANSFER to update the database





# **ERMES**











## **CHARACTERISTICS**

7" TOUCH SCREEN DISPLAY; LOG BOOK, AGENDA, GRAPHIC FUNCTIONS



AUTOMATIC WORKING CYCLE No Manual taps



**FULL RECOVERY FUNCTIONS** 

AUTOMATIC OIL AND DYE INJECTION with 3 dedicated scale
2 BOTTLES FOR NEW OIL INJECTION AND 1 BOTTLE FOR USED OIL
HERMETIC OIL AND DYE BOTTLES (Option)
HEATER BELT MOUNTED
PRINTER
USB PORT
INTERNAL DATA BASE
ANTIDUST BLANKET INCLUDED
STATUS INDICATORS
ETHERNET CONNECTION



INTEGRATED AUTOMATIC NITROGEN LEAK CHECK



READY TO USE ON HYBRID OR ELECTRIC CARS with rapid oil decontamination system



INTERNAL FLUSHING



A/C SYSTEM PROFESSIONAL FLUSHING (Option)



A/C SYSTEM DIAGNOSYS

INTERNAL 1234YF REFRIGERANT IDENTIFIER (Option)

	CODE	DESCRIPTION	
	ACC-88-289H		
# # 🛓	STARTPACK-HERMETIC	Hermetic Bottle 6 x Dye, 6 x Oil PAG 46, 6 x Oil POE	
	GAS ID GAS ID OPZ		
	Additional Accessories: CFU-NITRO.REDUCER, CFU-NITRO.HD, ACC-FLUSHING.YF	See at Special Tools Page 11	

#### SCF340R



#### SCF340H









### **CHARACTERISTICS**



AUTOMATIC WORKING CYCLE No Manual taps

**FULL RECOVERY FUNCTIONS** 

AUTOMATIC OIL AND DYE INJECTION with 1 dedicated scale

HERMETIC OIL AND DYE BOTTLES (Option)

HEATER BELT MOUNTED

**PRINTER** 

**USB PORT** 

INTERNAL DATA BASE

INCLUDED ANTIDUST BLANKET

STATUS INDICATORS



INTEGRATED AUTOMATIC NITROGEN LEAK CHECK



READY TO USE ON HYBRID OR ELECTRIC CARS with rapid oil decontamination system





INCLUDED BLUETOOTH CONNECTION for SmartPhone/Tablet/PC



INTERNAL FLUSHING



A/C SYSTEM PROFESSIONAL FLUSHING AND EASY FLUSH FUNCTION (Option)



A/C SYSTEM DIAGNOSYS

INTERNAL 1234YF REFRIGERANT IDENTIFIER (Option)

	CODE	DESCRIPTION
	ACC-88.072	Gas bottle fitting 1/4
	ACC-88.011	Straight adapter HP 1/4
	ACC-88-289H	Universal bottle Adapter 1234YF
# #	STARTPACK-HERMETIC	Hermetic Bottle 6 x Dye, 6 x Oil PAG 46, 6 x Oil POE
	GAS ID GAS ID OPZ	SAE J 2843 Internal 1234yf refrigerant identifier kit
	Additional Accessories: CFU-NITRO.REDUCER, CFU-NITRO.HD, ACC-FLUSHING, ACC-FLUSHING.YF, ACC-EASYFLUSH	See at Special Tools Page 11

## **FAST 320 / FAST 320YF**

## SCF320H

#### SCF320R











### **CHARACTERISTICS**



AUTOMATIC WORKING CYCLE No Manual taps

**FULL RECOVERY FUNCTIONS** 

AUTOMATIC OIL AND DYE INJECTION with 1 dedicated scale

HERMETIC OIL AND DYE BOTTLES (Option)

HEATER BELT MOUNTED

**PRINTER** 

**USB PORT** 

INTERNAL DATA BASE

INCLUDED ANTIDUST BLANKET

STATUS INDICATORS



READY TO CARRY OUT SEMIAUTOMATIC NITROGEN LEAK CHECK (Option)



READY TO USE ON HYBRID OR ELECTRIC CARS with rapid oil decontamination system





INCLUDED BLUETOOTH CONNECTION for SmartPhone/Tablet/PC



INTERNAL FLUSHING



A/C SYSTEM PROFESSIONAL FLUSHING AND EASY FLUSH FUNCTION (Option)



A/C SYSTEM DIAGNOSYS

INTERNAL 1234YF REFRIGERANT IDENTIFIER (Option)

	CODE	DESCRIPTION		
	ACC-88.072	Gas bottle fitting 1/4		
	ACC-88.011	Straight adapter HP 1/4		
	ACC-88-289H	Universal bottle Adapter 1234YF		
<b>* *</b>	STARTPACK-HERMETIC	Hermetic Bottle 6 x Dye, 6 x Oil PAG 46, 6 x Oil POE		
	GAS ID GAS ID OPZ	SAE J 2843 Internal 1234yf refrigerant identifier kit		
	Additional Accessories: CFU-NITRO, CFU-NITRO.HD, ACC-FLUSHING, ACC-FLUSHING.YF, ACC-EASYFLUSH	See at Special Tools Page 11		

#### SCF300R













### **CHARACTERISTICS**



AUTOMATIC WORKING CYCLE No Manual taps

**FULL RECOVERY FUNCTIONS** 

AUTOMATIC OIL INJECTION with 1 dedicated scale

AUTOMATIC DYE INIECTION (Option)

HERMETIC OIL AND DYE BOTTLES (Option)

HEATER BELT MOUNTED

PRINTER (Option)

**USB PORT** 

INTERNAL DATA BASE

ANTIDUST BLANKET (Option)



READY TO CARRY OUT SEMIAUTOMATIC NITROGEN LEAK CHECK (Option)



READY TO USE ON HYBRID OR ELECTRIC CARS





BLUETOOTH CONNECTION for SmartPhone/Tablet/PC



INTERNAL FLUSHING



A/C SYSTEM EASY FLUSH FUNCTION (Option)

A/C PRESSURE TEST

INTERNAL 1234YF REFRIGERANT IDENTIFIER (Option)

	CODE	DESCRIPTION		
	ACC-88.072	Gas bottle fitting 1/4		
	ACC-88.011	Straight adapter HP 1/4		
	ACC-88-289H	Universal bottle Adapter 1234YF		
	O-PK000092	Kit for automatic Dye		
	O-PK000092-OPZ	Injection		
	O-PK00051	D : 1 1/2		
	PK00051 OPZ	Printer Kit		
# # 🖢	STARTPACK-HERMETIC	Hermetic Bottle 6 x Dye, 6 x Oil PAG 46, 6 x Oil POE		
	GASID	SAE J 2843 Internal		
	GAS ID OPZ	1234yf refrigerant identifier kit		
	ACC-BLK-FAST	Antidust Blanket		
	Additional Accessories: CFU-NITRO, CFU-NITRO.HD, ACC-EASYFLUSH	See at Special Tools Page 11		

## **ECOS** 300 / **ECOS** 300YF

### SCE300R



#### SCE300H









## **CHARACTERISTICS**



AUTOMATIC WORKING CYCLE No Manual taps



FULL RECOVERY FUNCTIONS

AUTOMATIC OR ASSISTED OIL INJECTION AUTOMATIC OR ASSISTED DYE INJECTION (Option)

HEATER BELT MOUNTED

PRINTER (Option)

USB PORT

INTERNAL DATA BASE

ANTIDUST BLANKET (Option)



READY TO CARRY OUT SEMIAUTOMATIC NITROGEN LEAK CHECK (Option)



READY TO USE ON HYBRID OR ELECTRIC CARS





BLUETOOTH CONNECTION for SmartPhone/Tablet/PC



INTERNAL FLUSHING



A/C SYSTEM EASY FLUSH FUNCTION (Option)

A/C PRESSURE TEST

CODE	DESCRIPTION
ACC-88.072	Gas bottle fitting 1/4
ACC-88.011	Straight adapter HP 1/4
ACC-88-289H	Universal bottle Adapter 1234YF
O-PK000093 O-PK000093-OPZ	Kit for automatic Dye Injection
 O-PK00051 PK00051 OPZ	Printer Kit
ACC-BLK-ECOS	Antidust Blanket
Additional Accessories: CFU-NITRO, CFU-NITRO.HD, ACC-EASYFLUSH	See at Special Tools Page 11

## **AGRICOLD / AGRICOLD** YF

#### **FKG200**



#### FKG200YF









## **CHARACTERISTICS**

ANTI DE-CALIBRATION SCALE SYSTEM



AUTOMATIC WORKING CYCLE No Manual taps



**FULL RECOVERY FUNCTIONS** 

AUTOMATIC OR ASSISTED OIL INJECTION AUTOMATIC OR ASSISTED DYE INJECTION (Option)

HEATER BELT MOUNTED

PRINTER (Option)

**USB PORT** 

INTERNAL DATA BASE



READY TO CARRY OUT SEMIAUTOMATIC NITROGEN LEAK CHECK (Option)



READY TO USE ON HYBRID OR ELECTRIC CARS with rapid oil decontamination function (Option)



INTERNAL FLUSHING



A/C SYSTEM PROFESSIONAL FLUSHING (Option)

A/C PRESSURE TEST

CODE	DESCRIPTION	
ACC-88.072	Gas bottle fitting 1/4	
ACC-88.011	Straight adapter HP 1/4	
ACC-88-289H	Universal bottle Adapter 1234YF	
O-PK000092 O-PK00092 OPZ	Kit for automatic Dye Injection	
 O-PK00051 PK00051 OPZ	Printer Kit	
OAC0003 OAC-0003 YF	Hybrid vehicles kit	
OAC0002	12 V POWER SUPPLY	
Additional Accessories: CFU-NITRO, CFU-NITRO.HD, ACC-FLUSHING, ACC-FLUSHING.YF	See at Special Tools Page 11	









0000

### **CHARACTERISTICS**

SPECIALLY DESIGNED FOR BUS



AUTOMATIC WORKING CYCLE No Manual taps



**FULL RECOVERY FUNCTIONS** 

AUTOMATIC OIL AND DYE INJECTION with 1 dedicated scale

HEATER BELT MOUNTED

PRINTER (Option)

**USB PORT** 

INTERNAL DATA BASE



READY TO CARRY OUT SEMIAUTOMATIC NITROGEN LEAK CHECK (Option)



READY TO USE ON HYBRID OR ELECTRIC CARS with rapid oil decontamination function



INTERNAL FLUSHING



A/C SYSTEM PROFESSIONAL FLUSHING (Option)



A/C SYSTEM DIAGNOSYS

CODE	DESCRIPTION	
ACC-88.072	Gas bottle fitting 1/4	
ACC-88.011	Straight adapter HP 1/4	
O-PK00051 PK00051 OPZ	Printer Kit	
GEAR PUMP	1 Liter minute gear pump	
Additional Accessories: CFU-NITRO, CFU-NITRO.HD, ACC-FLUSHING,	See at Special Tools Page 11	

# **SPECIAL TOOLS**

OI EGIAE 100E0		
NITROGEN LEACK CHECK	CODE	DESCRIPTION
	CFU-NITRO	Kit for connection of 1l bottle to A/C Station - Inclusive of:  Box Pressure Reducer for 1l bottle 30cm hose with tap Manifold for connection A/C station Tank Holder
	CFU-NITRO.HD.XX	Kit for connection of 200 bar bottle to A/C Station - Inclusive of:  Box Pressure Reducer for 200 bar bottle 1,5m Hose Manifold for connection A/C station IT (Italy) DE (Germany, Poland) FR (France, Spain, Portugal) GB (United Kingdom)
	CFU-NITRO.CONNECT	Kit to connect CFU-NITRO or CFU-NITRO.HD direct to the vehicle A/C System for R134a and 1234yf - Inclusive of:  • Manometer • 1,5m Hose • HP connector for R134a e 1234yf
	RCD00.XX	Adapter from 200 Bar to 1 liter bottle IT (Italy) DE (Germany, Poland) FR (France, Spain, Portugal) GB (United Kingdom)
	CFU-NITRO.REDUCER	Kit to connect 1 liter bottle pressure reducer and hose to ERMES and FAST 340
	CFU-12.033 CFU-12.036	Electronic sniffer for R134a e 1234yf  Electronic sniffer for NItrogen / Hydrogen
	CFU-13.200 CFU-13.209	Nltrogen Bottle 1I Nitrogen Hidrogen bottle 1I
FLUSHING	CODE	DESCRIPTION
Expension Valve Expension Valve Compressor  Expension Valve  Receiver Other  LP line out	ACC-FLUSHING ACC-FUSHING.YF	Professional Refrigerant R134a Flushing Kit Professional Refrigerant 1234yf Flushing Kit
	ACC-EASYFLUSH	A/C Flushing and Oil Cleaning

## **SPECIAL TOOLS**

GAS IDENTIFIER	CODE	DESCRIPTION
Trico	MINI-ID MINI-ID 134	Portable 1234yf identifier Portable 134a identifier
GENERAL RECOVERY	CODE	DESCRIPTION
	ACC-UNREC-3/4CV ACC-UNREC-1CV	Universal recovery unit
	ACC-RECKIT-HFO-3/4CV ACC-RECKIT-HFO-1CV	Complete Recovery kit

# **ADDITIVES/LEAK DETECTION/ACCESSORIES**

OIL ADDITIVES	CODE	DESCRIPTION
Oksys PAG 45 PAG 45 PAG 500 PA	ADD-611.029 ADD-611.029YF ADD-611.030 ADD-611.030YF ADD-611.031 ADD-611.080.U ADD-611.045 ADD-611.024	PAG46 Oil for compressors for 134a - 6x250 ml PAG46 Oil for compressors for 1234YF - 6x250 ml PAG100 Oil for compressors for 134a - 6x250 ml PAG100 Oil for compressors for 1234YF - 6x250 ml PAG150 Oil for compressors for 134a - 6x250 ml PAG150 Oil for compressors for 134a - 6x250 ml POE80 - Compr. oil Hybrids R134a and 1234yf - 6x250 ml (Dielectric Strength 75KW/2,5mm) PAO68 Oil for compressors - 6x250 ml Antibacterial spray 6x200 ml
HERMETIC OIL ADDITIVES	CODE	DESCRIPTION
	ADD-AC55046A ADD-AC55046Y ADD-AC55100A ADD-AC55100Y ADD-AC54085A ADD-AC54085Y ADD-AC2188A	PAG46 Oil for compressors - for refrigerant R134a, 1234yf vehicles 6x250 ml PAG46 HERMETIC Bottle Oil for compressors - for refrigerant R134a, 1234yf 6x260 ml PAG100 Oil for compressors - for refrigerant R134a, 1234yf 6x250 ml PAG100 HERMETIC Bottle Oil for compressors for refrigerant R134a, 1234yf 6x260 ml POE80 - Compr. oil Hybrids - 6x250ml (Dielectric Strength 75KW/2,5mm) POE80 - HERMETIC Bottle Compr. oil Hybrids - 6x260ml (Dielectric Strength 75KW/2,5mm) PAO68 Oil for compressors - 6x250 ml
DYE ADDITIVES	CODE	DESCRIPTION
The state of the s	CFU-611.005.U CFU-611.801.U CFU-11.800/60P CFU-11.800/60YF	Dye for R134a and 1234yf systems - pack of 6 bottle of 250 ml 6 Boxes of 12 x 7,5 ml Dye syringes for R134a and 1234yf 60 ml syringe hose with non-return valve and quick coupler 60 ml syringe hose with non-return valve and quick coupler for 1234YF

HERMETIC DYE ADDITIVES	CODE	DESCRIPTION
C. Calabara Control Control	CFU-GL1234A CFU-GL1234-125Y	Dye for R134a, 1234yf and Hybrid systems - pack of 6 bottle of 250 ml  Dye for R134a, 1234yf and Hybrid systems - pack of 6 HERMETIC bottles of 125 ml
LEACK DETECTION ACCESSORIES	CODE	DESCRIPTION
	CFU-13.041 CFU-13.041YF	Piston dye/oil injector for R134a Piston dye/oil injector for 1234YF
	CFU-611.021T CFU-12.008 CFU-12.003	Dye remover-multi purpose cleaner spray pack of 6 cans of 400 ml UV leak detection lamp with glasses UV Lamp 60W incl glasses
SERVICE	CODE	DESCRIPTION
	ADD-11.039 FLT002 FLT003	Oil for vacuum pump 500 ml bottle  Dehitrating filter for families ECOS-FAST-ERMES - AGRICOLD  Dehitrating filter for HD202
ACCESSORIES	CODE	DESCRIPTION
# #	ACC-13.038YF	FORD FIESTA low pressure extension
	ACC-13.039YF	FORD FIESTA high pressure extension
	ACC-13.038D ACC-13.038DYF	BMW Quick coupling
	ACC-13.095 ACC-13-095YF	Renault Quick coupler
	RCD0005	LP quick connection (R134a)
	RCD0006	HP quick connection (R134a)
	RCD0007	LP quick connection (HFO1234yf)
	RCD0008	HP quick connection (HFO1234yf)
	ACC-12.026	Digital Thermometer
Succession 1	ACC-9000009-10	Packing of 10 paper rolls for printer 57mm dia 33mm
	ACC-13.092	Protective gloves
	TBZ0001	LP hose 3 m (blue) (HFO1234yf)
	TBZ0002	HP hose 3 m (red) (HFO1234yf)
	TBZ0003	LP hose 3 m (blue) (R134a)
	TBZ0004	HP hose 3 m (red) (R134a)
	ACC-HS75set2	Set of 2 hoses 7,5 m (R134a)
9.90	ACC-HS75set2 YF	Set of 2 hoses 7,5 m (1234YF)
	ACC-5SGLAS-F	Replacement filter for AC flushing 5 units

RANGE	R134a			R134 REFRIGERANT	R1234yf
MODEL	FAST 340	FAST 320	FAST 300	ECOS 300	ERMES YF
TECHNICAL FEATURES					
Process	Fully Automatic	Fully Automatic	Fully Automatic	Fully Automatic	Fully Automatic
Display	Graphic LCD 264x64 Pixel	Graphic LCD 264x64 Pixel	Graphic LCD 128x64 Pixel	Graphic LCD 128x64 Pixel	7" Color Graphic Display Touch Screen
Full Recovery Function	YES	YES	YES	YES	YES
Tank Capacity	18 Kg	18 Kg	12 Kg	9 Kg	15 Kg
Heater Belt	YES	YES	YES	YES	YES
Scale Accuracy	+/- 5 g	+/- 5 g	+/- 5 g	+/- 5 g	+/- 5 g
Automatic Oil Injection	YES 1 Scale	YES 1 Scale	YES 1 Scale	YES	YES 3 Scale
Automatic Dye Injection	YES 1 Scale	YES 1 Scale	Option	Option	YES
Printer	YES	YES	Option	Option	YES
Compressor	10 cc	10 cc	10 cc	10 cc	10 cc
Vacuum Pump	100 l/min	100 l/min	70 l/min	70 I/min	100 l/min
Air Purge	Automatic High Precision	Automatic	Automatic	Automatic	Automatic High Precision
Hermetic Oil and Dye bottles	Option	Option	Option	NO	Option
Stauts Indicators	YES	YES	NO	NO	YES
Data Base	YES	YES	YES	YES	YES
Graphic data base	YES	YES	NO	NO	YES
A/C Diagnostic / AC Pressure Test	YES	YES	AC Pressure Test Only	AC Pressure Test Only	YES
Hybrid Function	YES Rapid oil decontamination	YES Rapid oil decontamination	YES	YES	YES Rapid oil decontamination
Nitrogen Leak Check	Automatic	Option/Semiautomatic	Option/Semiautomatic	Option/Semiatomatic	Automatic
Refrigerant 1234yf Identifier	NO	NO	NO	NO	Option
PC data transfer	YES	YES	YES	YES	YES
A/C Flushing Kit	Option	Option	Option (EASY FLUSH only)	Option (EASY FLUSH only)	Option
Bluetooth Connection	YES	YES	YES	YES	NO
Remote Control / Interface	YES via Bluetooth	YES via Bluetooth	YES via Bluetooth	YES via Bluetooth	NO
Charging Gear Pump	NO	NO	NO	NO	NO
12 V Power Supply	NO	NO	NO	NO	NO
Power Supply	220V 50 Hz	220V 50 Hz	220V 50 Hz	220V 50 Hz	220V 50 Hz
Dimensions	58x55x120 cm	58x55x120 cm	51x48x94 cm	51x48x94 cm	56x61x125 cm
Weight	60/70 Kg	60/70 Kg	55/65 Kg	55/65 Kg	95 Kg
SCOPE OF DELIVERY				,	
Hp LP Quick Couplers	Included	Included	Included	Included	Included
Hoses	3m	3m	3m	3m	3m
Blanket	YES	YES	Option	Option	YES
Power Cord	YES	YES	YES	YES	YES
Calibration Handle	YES	YES	YES	YES	YES
Extra oil bottle	YES	YES	YES	YES	YES
2 x temperature probes	Included	Included	NO	NO	Included

			WFO-1234Y REFRIGERANT	AGRI		Heavy Duty
FAST 340YF	FAST 320YF	FAST 300YF	ECOS 300YF	AGRICOLD	AGRICOLD YF	HD 202
Fully Automatic	Fully Automatic	Fully Automatic	Fully Automatic	Fully Automatic	Fully Automatic	Fully Automatic
Graphic LCD 264x64 Pixel	Graphic LCD 264x64 Pixel	Graphic LCD 128x64 Pixel	Graphic LCD 128x64 Pixel	Graphic LCD 264x64 Pixel	Graphic LCD 264x64 Pixel	Graphic LCD 264x64 Pixel
YES	YES	YES	YES	YES	YES	YES
12 Kg	12 Kg	9 Kg	9 Kg	12 Kg	12 Kg	40 Kg
YES	YES	YES	YES	YES	YES	YES
+/- 5 g	+/- 5 g	+/- 5 g	+/- 5 g	+/- 5 g	+/- 5 g	+/- 5 g
YES 1 Scale	YES 1 Scale	YES 1 scale	YES	YES	YES	YES 1 scale
YES 1 Scale	YES 1 Scale	Option	Option	Option	Option	YES 1 scale
YES	YES	Option	Option	Option	Option	Option
10 cc	10 cc	10 cc	10 cc	10 cc	10 cc	20 cc
100 L/min	100 L/min	70 L/min	70 L/min	100 L/min	100 L/min	200 L/min Dual Stage
Automatic High Precision	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic
Option	Option	Option	NO	NO	NO	NO
YES	YES	NO	NO	NO	NO	NO
YES	YES	YES	YES	YES	YES	YES
YES	YES	NO	NO	NO	NO	NO
YES	YES	AC Pressure Test Only				
YES Rapid oil decontamination	YES Rapid oil decontamination	YES	YES	Option (Rapid)	Option (Rapid)	YES Rapid oil decontamination
Automatic	Option/Semiautomatic	Option/Semiautomatic	Option/Semiautomatic	Option/Semiautomatic	Option/Semiautomatic	Option/Semiautomatic
Option	Option	Option	NO	NO	NO	NO
YES	YES	YES	YES	YES	YES	YES
Option	Option	Option (EASY FLUSH only)	Option (EASY FLUSH only)	Option	Option	Option
YES	YES	YES	YES	NO	NO	NO
YES via Bluetooth	YES via Bluetooth	YES via Bluetooth	YES via Bluetooth	NO	NO	NO
NO	NO	NO	NO	NO	NO	Option
NO	NO	NO	NO	Option	Option	NO
220V 50 Hz	220V 50 Hz	220V 50 Hz	220V 50 Hz	220V 50 Hz 12V DC	220V 50 Hz 12V DC	220V 50 Hz
58x55x120 cm	58x55x120 cm	51x48x94 cm	51x48x94 cm	48x68x88 cm	48x68x88 cm	50x75x115 cm
60/70 Kg	60/70 Kg	55/65 Kg	55/65 Kg	60/70 Kg	60/70 Kg	90/110 Kg
Included	Included	Included	Included	Included	Included	Included
3m	3m	3m	3m	7,5 m	7,5 m	3 m
YES	YES	Option	Option	NO	NO	NO
YES	YES	YES	YES	YES	YES	YES
YES	YES	YES	YES	YES	YES	YES
YES	YES	YES	YES	Option	Option	YES
Included	Included	NO	NO	NO	NO	NO





## STROVOLOS INDUSTRIAL AREA

P.O. BOX 27077

1641 NICOSIA

TEL.: +357 22 510420

FAX: +357 22 493955

gk\_son@spidernet.com.cy





www.koutsoullis.com www.oksys.com